Penfect PATIO DOOR SYSTEM





PERFECT PATIO DOOR SYSTEM **FEATURES AND BENEFITS**

- All vinyl, multi-chamber profile design for superior insulating properties for your comfort and energy savings.
- Mechanically-joined frame with accessory groove in standard 5-5/8" frame depth.
- Mechanically fastened aluminum reinforced door panels for rigidity and strength.
- Standard sizes available: 5, 6 or 8' width by 6'8" or 8'0" height.
- AAMA certified zinc-plated, double tandem nylon rollers for durability and smooth, effortless sliding.
- Corrosion-resistant, anodized-aluminum tracks for ongoing, smooth gliding operation.
- Full perimeter triple layer weather stripping for excellent air and water tightness.
- Standard "landmark" handle (with lock and key upgrade) and available upgrade to "Prestige" series handles.
- Heavy-duty screen with heavy-gauge extruded aluminum frame and fiberglass mesh for solid frame and smooth operation.
- Specially formulated, color-matched sealing material for durability in performance and color retention.
- Specially-designed fabrication equipment combined with some of the most efficient manufacturing processes ensure that the fit, finish and functionality of a PERFECT© brand sliding Patio Door is of the highest quality.

Weatherstrip 5-5/8" Jamb 7/8" or 1" Low-E with deep Argon glass pockets **FOOT LOCK NYLON ROLLER**

CONTEMPORARY HANDLE



PRESTIGE HANDLE

UPGRADE



COLOURS

	Cream LG 492	Dover Gray 536	Pebble 559	Commercial Brown 562
	Almond 532	Storm 570	Sandalwood 508	Espresso 5P3
	Maize 502	Slate 523	Brownstone 571	Graphite 5P5
	Wicker 538	Windswept Smoke 506	Dark Drift 557	Iron Ore 5P6
	Canyon Clay 510	Chestnut Brown 554	Sable LG	Black 525
COLORS SHOWN SHOULD BE USED AS GENERAL GUIDES. PRINTED COLORS ARE NOT AN EXACT				

MATCH FOR EXTRUDED OR PAINTED VINYL.

MINI BLINDS


Mechanically-joined





CONFIGURATIONS

OX AND XO 2 PANEL



2 PANEL OX AND XO: **5068** - 59 5/8" X 79 5/8' **5068** MICHIGAN

58 5/8" X 79 5/8" 6068 - 71 5/8" X 79 5/8' 6068 MICHIGAN 8068 - 95 5/8" X 79 5/8"

OXO/OZO 3 PANEL



3 PANEL OXO:

7068 - 89 3/8" X 79 5/8" 1268 - 143 3/8" X 79 5/8"

OXXO 4 PANEL

Aluminum track cover

Fixed panel

4 PANEL OXXO:

Fixed support

ALL ABOVE SIZES ARE ALSO AVAILABLE IN STANDARD 8 FT. HIGH CONFIGURATIONS HEIGHT CHANGES TO 95 5/8"



- · Performance Alr: A3 Water: 440 Pa Structural: DP-40 (8068) R-PG40(8068) Door: 96"x 80" (AAMA/WDMA/CSA 101/1.S.2/A440-11 and CSA A440S1-09)
- · Tempered 7/8 " Insulated Glass Units
- · LoE180: U-Value: 1.70 SHGC: 0.53
- · LoE180 + 189: U-Value: 1.42 SHGC: 0.49
- · LoE366 + 189: U-Value: 1.42 SHGC: 0.21